




## VR EVO 12 AND 12-S

### SPECIFICATIONS

|   |
|---|
| <b>Part numbers:</b> 103254 (VR EVO 12), 103255 (VR EVO 12-S)                           |
| <b>Rated line pull:</b> 12,000 lbs. (5443 kg) single-line                               |
| <b>Motor:</b> 12V DC, series wound  |
| <b>Electrical controls:</b> Albright Contactor  |
| <b>Remote Control:</b> 2-in-1 plug-in remote, wireless capability and 11.5' (3.5m) lead |
| <b>Geartrain:</b> 3-stage planetary   |
| <b>Gear ratio:</b> 234:1  |
| <b>Clutch (freespooling):</b> Rotating ring gear clutch                                 |
| <b>Brake:</b> Spring Brake  |
| <b>Drum diameter/Length:</b> Steel and Synthetic: 2.5" / 9.0" (6.73cm / 23cm)           |
| <b>Rope:</b> Steel: 3/8" x 85' (9.5mm x 25.9m)<br>Synthetic: 3/8" x 90' (9.5mm x 27.4m) |
| <b>Fairlead:</b> Steel: Roller, Synthetic: Die Cast Hawse                               |
| <b>Recommended Battery:</b> 650 CCA minimum for winching                                |
| <b>Battery leads:</b> 0.98" x 6.5' (25mm x 2m)  |
| <b>Finish:</b> Powder coating over primer undercoating                                  |
| <b>Weight:</b> VR EVO 12: 90.8 lbs. (41.2 kg),<br>VR EVO 12-S: 72.3 lbs. (32.8 kg)      |
| <b>Warranty:</b> Limited lifetime   |

### DIMENSIONS



|                         |                          |
|-------------------------|--------------------------|
| <b>A</b> 21.02" (534mm) | <b>E</b> 4.84" (123mm)   |
| <b>B</b> 10.08" (256mm) | <b>F</b> 6.18" (157mm)   |
| <b>C</b> 2.54" (64mm)   | <b>G</b> 7.5" (191.4mm)  |
| <b>D</b> 10" (254mm)    | <b>H</b> 6.79" (172.4mm) |

Mounting bolt pattern: 10.0" x 4.5" (254mm x 114.3mm)

#### 12V DC PERFORMANCE SPECS (first layer)

| Line Pull    | Line Speed           | Motor    | Pull by layer:  |
|--------------|----------------------|----------|-----------------|
| Lbs. (kg)    | Ft./min.<br>(M/min.) | Current  | layer/Lbs. (kg) |
| 0            | 26.2 (8.0)           | 55 amps  | 1/12000 (5443)  |
| 2000 (910)   | 13.9 (4.2)           | 120 amps | 2/9517 (4317)   |
| 4000 (1810)  | 9.5 (2.9)            | 178 amps | 3/7886 (3577)   |
| 6000 (2720)  | 8.1 (2.5)            | 234 amps | 4/6732 (3054)   |
| 8000 (3630)  | 6.8 (2.1)            | 288 amps | 5/5872 (2664)   |
| 10000 (4536) | 4.9 (1.5)            | 337 amps |                 |
| 12000 (5440) | 4.0 (1.2)            | 396 amps |                 |




## VR EVO 10 AND 10-S

### SPECIFICATIONS

|   |
|---|
| <b>Part numbers:</b> 103252 (VR EVO 10), 103253 (VR EVO 10-S)                           |
| <b>Rated line pull:</b> 10,000 lbs. (4536 kg) single-line                               |
| <b>Motor:</b> 12V DC, series wound  |
| <b>Electrical controls:</b> Albright Contactor  |
| <b>Remote Control:</b> 2-in-1 plug-in remote, wireless capability and 11.5' (3.5m) lead |
| <b>Geartrain:</b> 3-stage planetary   |
| <b>Gear ratio:</b> 218:1  |
| <b>Clutch (freespooling):</b> Rotating ring gear clutch                                 |
| <b>Brake:</b> Spring Brake  |
| <b>Drum diameter/Length:</b> Steel and Synthetic: 2.5"/9.0" (6.73cm/23cm)               |
| <b>Rope:</b> Steel: .354" x 90' (9mm x 27.4m)<br>Synthetic: 3/8" x 90' (9.5mm x 27.4m)  |
| <b>Fairlead:</b> Steel: Roller, Synthetic: Die Cast Hawse                               |
| <b>Recommended Battery:</b> 650 CCA minimum for winching                                |
| <b>Battery leads:</b> 0.98" x 6.5' (25mm x 2m)  |
| <b>Finish:</b> Powder coating over primer undercoating                                  |
| <b>Weight:</b> VR EVO 10: 91.9 lbs. (41.7 kg),<br>VR EVO 10-S: 72.4 lbs. (26 kg)        |
| <b>Warranty:</b> Limited lifetime   |

### DIMENSIONS



|                         |                          |
|-------------------------|--------------------------|
| <b>A</b> 21.02" (534mm) | <b>E</b> 4.84" (123mm)   |
| <b>B</b> 10.08" (256mm) | <b>F</b> 6.18" (157mm)   |
| <b>C</b> 2.54" (64mm)   | <b>G</b> 7.5" (191.4mm)  |
| <b>D</b> 10" (254mm)    | <b>H</b> 6.79" (172.4mm) |

Mounting bolt pattern: 10.0" x 4.5" (254mm x 114.3mm)

#### 12V DC PERFORMANCE SPECS (first layer)

| Line Pull    | Line Speed           | Motor    | Pull by layer   |
|--------------|----------------------|----------|-----------------|
| Lbs. (kg)    | Ft./min.<br>(M/min.) | Current  | layer/Lbs. (kg) |
| 0            | 27.1 (8.3)           | 58 amps  | 1/10000 (4536)  |
| 2000 (910)   | 13.9 (4.2)           | 125 amps | 2/7996 (3627)   |
| 4000 (1810)  | 9.9 (3.0)            | 185 amps | 3/6661 (3021)   |
| 6000 (2720)  | 8.2 (2.5)            | 244 amps | 4/5708 (2589)   |
| 8000 (3630)  | 6.5 (2.0)            | 303 amps | 5/4993 (2265)   |
| 10000 (4536) | 5.2 (1.6)            | 358 amps |                 |




## VR EVO 8 AND 8-S

### SPECIFICATIONS

|   |
|---|
| <b>Part numbers:</b> 103250 (VR EVO 8), 103251 (VR EVO 8-S)                             |
| <b>Rated line pull:</b> 8,000 lbs. (3629 kg) single-line                                |
| <b>Motor:</b> 12V DC, series wound  |
| <b>Electrical controls:</b> Albright Contactor  |
| <b>Remote Control:</b> 2-in-1 plug-in remote, wireless capability and 11.5' (3.5m) lead |
| <b>Geartrain:</b> 3-stage planetary   |
| <b>Gear ratio:</b> 218:1  |
| <b>Clutch (freespooling):</b> Rotating ring gear clutch                                 |
| <b>Brake:</b> Spring Brake  |
| <b>Drum diameter/Length:</b> Steel and Synthetic: 2.5"/9.0" (6.73cm/23cm)               |
| <b>Rope:</b> Steel: 5/16" x 90' (8mm x 27.4m)<br>Synthetic: 3/8" x 90' (9.5mm x 27.4m)  |
| <b>Fairlead:</b> Steel: Roller, Synthetic: Die Cast Hawse                               |
| <b>Recommended Battery:</b> 650 CCA minimum for winching                                |
| <b>Battery leads:</b> 0.98" x 6.5' (25mm x 2m)  |
| <b>Finish:</b> Powder coating over primer undercoating                                  |
| <b>Weight:</b> VR EVO 8: 83.5 lbs. (37.9 kg),<br>VR EVO 8-S: 72.4 lbs. (32.8 kg)        |
| <b>Warranty:</b> Limited lifetime   |

### DIMENSIONS



|                         |                          |
|-------------------------|--------------------------|
| <b>A</b> 21.02" (534mm) | <b>E</b> 4.84" (123mm)   |
| <b>B</b> 10.08" (256mm) | <b>F</b> 6.18" (157mm)   |
| <b>C</b> 2.54" (64mm)   | <b>G</b> 7.5" (191.4mm)  |
| <b>D</b> 10" (254mm)    | <b>H</b> 6.79" (172.4mm) |

Mounting bolt pattern: 10.0" x 4.5" (254mm x 114.3mm)

#### 12V DC PERFORMANCE SPECS (first layer)

| Line Pull   | Line Speed           | Motor    | Pull by layer   |
|-------------|----------------------|----------|-----------------|
| Lbs. (kg)   | Ft./min.<br>(M/min.) | Current  | layer/Lbs. (kg) |
| 0           | 24.8 (7.6)           | 57 amps  | 1/8000 (3630)   |
| 2000 (910)  | 13.1 (4.0)           | 122 amps | 2/6545 (2969)   |
| 4000 (1810) | 9.6 (2.9)            | 183 amps | 3/5538 (2512)   |
| 6000 (2720) | 7.6 (2.3)            | 242 amps | 4/4800 (2177)   |
| 8000 (3630) | 6.0 (1.8)            | 298 amps |                 |



## WARN VR EVO

### The New Standard in Standard-Duty Winches

With the lowest amp draw and fastest line speed under load, the new VR EVO series of winches are the hardest-working, standard-duty winches we've ever offered. They feature IP68-rated waterproof construction for performance in all conditions, a two-in-one wireless/corded remote that gives you options when winching, and our legendary reliability—standard. Plus, they're covered by our industry-leading limited lifetime warranty. All VR EVO winches are available at a price that won't pull you out of your budget.

- Available in 8,000, 10,000, and 12,000 lb. capacities
- Choice of durable steel or easy-to-handle synthetic rope
- Rugged, one-piece, cast-aluminum tie plate for added strength and durability
- Heavy-duty, die-cast hawse fairlead
- Two-in-one remote with wired and wireless controls for increased winching options
- Sealed Albright® contactor delivers the ultimate in reliability
- Control pack can be relocated for low-profile installations
- Limited lifetime warranty (mechanical), seven year electrical warranty

VR EVO is the gateway to the WARN brand and has the best warranty in the business—you can't afford to trust anything less.

**103254 VR EVO 12**  
85' of 3/8" steel rope and roller fairlead

**103255 VR EVO 12-S**  
90' of 3/8" synthetic rope and black hawse fairlead

**103252 VR EVO 10**  
90' of 0.3/8" steel rope and roller fairlead

**103253 VR EVO 10-S**  
90' of 3/8" synthetic rope and black hawse fairlead

**103250 VR EVO 8**  
90' of 5/16" steel rope and roller fairlead

**103251 VR8-S**  
90' of 3/8" synthetic rope and black hawse fairlead





## Center-Mounted Convertible Control Pack

You can mount the control pack separately from the winch, or keep it attached for an integrated look. Your choice.



## Two-in-one Remote

A versatile, two-in-one remote gives users the option, and security, of either wired or wireless connectivity when operating the winch. You have a full-range of options, whatever the terrain or circumstances.

